



# Courser® CXT™

## Tire Specifications Table

Tire Size	Load Range	Revs	Tire Weight	Single Max Load	Single Inflation Pressure	Dual Max Load	Dual Inflation Pressure	Static Loaded Radius	Tread Depth	Max Speed	Approved Rim Width	Overall Diameter	Overall Width	Overall Width Loaded
12.5/75R20	E	567 /mi	70 lbs	3,750 lbs	65 psi	-	-	-	18.5	99 mph	8.5-11.0 in	37 in	12 in	12 in
	F	596 /mi	67 lbs	3,640 lbs	80 psi	-	-	-	18.5	99 mph	8.5-11.0 in	35 in	13 in	13 in
12.5/75R20	-	352 /km	-	-	448 kPa	-	-	-	15 mm	-	-	940 mm	-	315 mm
	-	370 /km	-	-	551 kPa	-	-	-	15 mm	-	-	889 mm	-	318 mm
235/80R17	E	649 /mi	47 lbs	3,085 lbs	80 psi	2,835 lbs	80 psi	-	18.5	99 mph	6.0-7.5 in	-	9 in	9 in
		403 /km	-	-	551 kPa	-	-	-	15 mm	-	-	-	-	239 mm
235/85R16	E	649 /mi	46 lbs	3,042 lbs	80 psi	2,778 lbs	80 psi	-	18.5	99 mph	6.0-7.5 in	-	10 in	10 in
		403 /km	-	-	551 kPa	-	-	-	15 mm	-	-	-	-	246 mm
245/75R16	E	673 /mi	46 lbs	3,042 lbs	80 psi	2,778 lbs	80 psi	-	18.5	99 mph	6.5-8.0 in	-	9 in	9 in
		418 /km	-	-	551 kPa	-	-	-	15 mm	-	-	-	-	239 mm
245/75R17	E	651 /mi	49 lbs	3,195 lbs	80 psi	2,910 lbs	80 psi	-	18.5	99 mph	6.5-7.5 in	-	10 in	10 in
		405 /km	-	-	551 kPa	-	-	-	15 mm	-	-	-	-	244 mm
265/60R20	E	630 /mi	58 lbs	3,195 lbs	80 psi	2,910 lbs	80 psi	-	18.5	99 mph	7.5-9.5 in	-	11 in	11 in
		391 /km	-	-	551 kPa	-	-	-	15 mm	-	-	-	-	269 mm
265/70R17	E	650 /mi	54 lbs	3,195 lbs	80 psi	2,910 lbs	80 psi	-	18.5	99 mph	7.0-8.5 in	-	11 in	11 in
		404 /km	-	-	551 kPa	-	-	-	15 mm	-	-	-	-	274 mm
265/70R18	E	631 /mi	54 lbs	3,525 lbs	80 psi	3,195 lbs	80 psi	-	18.5	99 mph	7.0-9.0 in	-	11 in	11 in
		392 /km	-	-	551 kPa	-	-	-	15 mm	-	-	-	-	272 mm
265/75R16	E	650 /mi	51 lbs	3,415 lbs	80 psi	3,085 lbs	80 psi	-	18.5	99 mph	7.0-8.0 in	-	10 in	10 in
		404 /km	-	-	551 kPa	-	-	-	15 mm	-	-	-	-	257 mm
275/55R20	E	641 /mi	58 lbs	3,085 lbs	80 psi	2,835 lbs	80 psi	-	18.5	99 mph	7.5-9.5 in	-	11 in	11 in
		398 /km	-	-	551 kPa	-	-	-	15 mm	-	-	-	-	274 mm
275/65R18	E	641 /mi	54 lbs	3,415 lbs	80 psi	3,085 lbs	80 psi	-	18.5	99 mph	7.5-9.0 in	-	11 in	11 in
		398 /km	-	-	551 kPa	-	-	-	15 mm	-	-	-	-	279 mm
275/65R20	E	598 /mi	63 lbs	3,750 lbs	80 psi	3,415 lbs	80 psi	-	18.5	99 mph	7.5-9.5 in	-	12 in	12 in
		372 /km	-	-	551 kPa	-	-	-	15 mm	-	-	-	-	292 mm
275/70R18	E	620 /mi	57 lbs	3,640 lbs	80 psi	3,305 lbs	80 psi	-	18.5	99 mph	7.0-8.5 in	-	11 in	11 in
		385 /km	-	-	551 kPa	-	-	-	15 mm	-	-	-	-	279 mm

285/55R20	E	636 /mi 395 /km	59 lbs	3,305 lbs	80 psi 551 kPa	3,000 lbs	80 psi 551 kPa	-	18.5 15 mm	99 mph	8.0-10.0 in	-	12 in	12 in 297 mm
285/60R20	E	612 /mi 380 /km	64 lbs	3,640 lbs	80 psi 551 kPa	3,305 lbs	80 psi 551 kPa	-	18.5 15 mm	99 mph	8.0-10.0 in	-	11 in	11 in 290 mm
285/65R18	E	628 /mi 390 /km	58 lbs	3,640 lbs	80 psi 551 kPa	3,305 lbs	80 psi 551 kPa	-	18.5 15 mm	99 mph	8.0-10.0 in	-	12 in	12 in 292 mm
285/70R17	E	627 /mi 390 /km	58 lbs	3,195 lbs	80 psi 551 kPa	2,910 lbs	80 psi 551 kPa	-	18.5 15 mm	99 mph	7.5-9.0 in	-	12 in	12 in 292 mm
285/75R16	E	628 /mi 390 /km	57 lbs	3,750 lbs	80 psi 551 kPa	3,415 lbs	80 psi 551 kPa	-	18.5 15 mm	99 mph	7.5-9.0 in	-	11 in	11 in 287 mm
285/75R17	E	607 /mi 377 /km	60 lbs	3,195 lbs	80 psi 551 kPa	2,910 lbs	80 psi 551 kPa	-	18.5 15 mm	99 mph	7.5-9.5 in	-	12 in	12 in 292 mm
295/70R17	E	617 /mi 383 /km	60 lbs	3,195 lbs	80 psi 551 kPa	2,910 lbs	80 psi 551 kPa	-	18.5 15 mm	99 mph	7.5-10.0 in	-	12 in	12 in 300 mm
295/70R18	E	603 /mi 375 /km	63 lbs	4,080 lbs	80 psi 551 kPa	3,750 lbs	80 psi 551 kPa	-	18.5 15 mm	99 mph	7.5-10.0 in	-	12 in	12 in 305 mm
305/55R20	F	620 /mi 385 /km	64 lbs	3,640 lbs	80 psi 551 kPa	3,305 lbs	80 psi 551 kPa	-	18.5 15 mm	99 mph	8.5-11.0 in	-	13 in	13 in 318 mm
31/10.5R15	C	674 /mi 419 /km	45 lbs	2,270 lbs	50 psi 344 kPa	-	-	-	18.5 15 mm	99 mph	7.0-9.0 in	31 in 787 mm	11 in	11 in 277 mm
315/70R17	D	599 /mi 372 /km	67 lbs	3,195 lbs	50 psi 344 kPa	2,910 lbs	50 psi 344 kPa	-	18.5 15 mm	99 mph	8.0-11.0 in	-	13 in	13 in 325 mm
33/12.5R15	C	630 /mi 391 /km	57 lbs	2,205 lbs	35 psi 241 kPa	-	-	-	18.5 15 mm	99 mph	8.5-11.0 in	33 in 838 mm	12 in	12 in 307 mm