



# Courser® HXT™

## Tire Specifications Table

Tire Size	Load Range	Revs	Tire Weight	Single Max Load	Single Inflation Pressure	Dual Max Load	Dual Inflation Pressure	Static Loaded Radius	Tread Depth	Max Speed	Approved Rim Width	Overall Diameter	Overall Width	Overall Width Loaded
185/60R15	C	872 /mi	23 lbs	1,477 lbs	55 psi	1,389 lbs	55 psi	-	14	118 mph	5.5-6.0 in	-	7 in	7 in
		542 /km			379 kPa		379 kPa		11 mm					
215/85R16	E	684 /mi	35 lbs	2,680 lbs	80 psi	2,470 lbs	80 psi	-	14.5	106 mph	5.5-7.0 in	-	8 in	8 in
		425 /km			551 kPa		551 kPa		12 mm					
225/75R16	E	710 /mi	36 lbs	2,680 lbs	80 psi	2,470 lbs	80 psi	-	14.5	106 mph	6.0-7.0 in	-	9 in	9 in
		441 /km			551 kPa		551 kPa		12 mm					
235/65R16	E	740 /mi	37 lbs	3,195 lbs	85 psi	3,000 lbs	85 psi	-	14.5	106 mph	6.5-7.5 in	-	9 in	9 in
		460 /km			586 kPa		586 kPa		12 mm					
235/75R15	C	717 /mi	34 lbs	1,985 lbs	50 psi	1,820 lbs	50 psi	-	14	106 mph	6.0-7.0 in	-	9 in	9 in
		446 /km			344 kPa		344 kPa		11 mm					
235/80R17	E	653 /mi	41 lbs	3,085 lbs	80 psi	2,835 lbs	80 psi	-	14.5	106 mph	6.0-7.5 in	-	9 in	9 in
		406 /km			551 kPa		551 kPa		12 mm					
235/85R16	E	653 /mi	40 lbs	3,042 lbs	80 psi	2,778 lbs	80 psi	-	14.5	106 mph	6.0-7.5 in	-	9 in	9 in
		406 /km			551 kPa		551 kPa		12 mm					
245/70R17	E	679 /mi	41 lbs	3,000 lbs	80 psi	2,755 lbs	80 psi	-	14.5	112 mph	6.5-8.0 in	-	10 in	10 in
		422 /km			551 kPa		551 kPa		12 mm					
245/75R16	E	683 /mi	41 lbs	3,042 lbs	80 psi	2,778 lbs	80 psi	-	14.5	106 mph	6.5-8.0 in	-	10 in	10 in
		424 /km			551 kPa		551 kPa		12 mm					
245/75R17	E	658 /mi	44 lbs	3,195 lbs	80 psi	2,910 lbs	80 psi	-	14.5	112 mph	6.5-7.5 in	-	10 in	10 in
		409 /km			551 kPa		551 kPa		12 mm					
265/70R17	E	655 /mi	47 lbs	3,195 lbs	80 psi	2,910 lbs	80 psi	-	14.5	112 mph	7.0-8.5 in	-	11 in	11 in
		407 /km			551 kPa		551 kPa		12 mm					
265/70R18	E	635 /mi	49 lbs	3,525 lbs	80 psi	3,195 lbs	80 psi	-	14.5	112 mph	7.0-9.0 in	-	11 in	11 in
		395 /km			551 kPa		551 kPa		12 mm					
265/75R16	E	656 /mi	46 lbs	3,415 lbs	80 psi	3,085 lbs	80 psi	-	14.5	106 mph	7.0-8.0 in	-	11 in	11 in
		408 /km			551 kPa		551 kPa		12 mm					
275/65R18	E	646 /mi	50 lbs	3,415 lbs	80 psi	3,085 lbs	80 psi	-	14.5	112 mph	7.5-9.5 in	-	11 in	11 in
		401 /km			551 kPa		551 kPa		12 mm					

		606 /mi	54 lbs	3,750 lbs	80 psi	3,415 lbs	80 psi	-	14	112 mph	7.5-9.5 in	-	11 in	11 in
275/65R20	E	377 /km			551 kPa		551 kPa	-	11 mm			-		282 mm
		624 /mi	52 lbs	3,640 lbs	80 psi	3,305 lbs	80 psi	-	14.5	112 mph	7.0-8.5 in	-	11 in	11 in
275/70R18	E	388 /km			551 kPa		551 kPa	-	12 mm			-		282 mm
		637 /mi	51 lbs	3,750 lbs	80 psi	3,415 lbs	80 psi	-	14.5	106 mph	7.5-9.0 in	-	12 in	12 in
285/75R16	E	396 /km			551 kPa		551 kPa	-	12 mm			-		295 mm