



Course Trail™ Tire Specifications Table

Tire Size	Load Range	Revs	Tire Weight	Single Max Load	Single Inflation Pressure	Dual Max Load	Dual Inflation Pressure	Static Loaded Radius	Tread Depth	Max Speed	Approved Rim Width	Overall Diameter	Overall Width	Overall Width Loaded
225/65R17	SL	724 /mi	31 lbs	1,874 lbs	44 psi	-	-	-	12.5	130 mph	6.0-8.0 in	-	9 in	9 in
		450 /km			303 kPa				10 mm					
225/75R16	SL	712 /mi	28 lbs	1,984 lbs	44 psi	-	-	-	13.5	118 mph	6.0-7.5 in	-	9 in	9 in
		442 /km			303 kPa				11 mm					
235/65R17	XL	710 /mi	34 lbs	2,205 lbs	50 psi	-	-	-	13	130 mph	6.5-8.5 in	-	10 in	10 in
		441 /km			344 kPa				10 mm					
235/70R16	SL	719 /mi	32 lbs	2,094 lbs	44 psi	-	-	-	13.5	118 mph	6.0-8.0 in	-	9 in	9 in
		447 /km			303 kPa				11 mm					
235/75R15	XL	721 /mi	32 lbs	2,271 lbs	50 psi	-	-	-	14	118 mph	6.0-8.0 in	-	9 in	9 in
		448 /km			344 kPa				11 mm					
235/75R17	SL	674 /mi	34 lbs	2,271 lbs	44 psi	-	-	-	14	118 mph	6.0-8.0 in	-	9 in	9 in
		419 /km			303 kPa				11 mm					
245/60R18	SL	698 /mi	31 lbs	2,039 lbs	44 psi	-	-	-	12	130 mph	7.0-8.5 in	-	10 in	10 in
		434 /km			303 kPa				10 mm					
245/65R17	XL	702 /mi	35 lbs	2,403 lbs	50 psi	-	-	-	13	118 mph	7.0-8.5 in	-	10 in	10 in
		436 /km			344 kPa				10 mm					
245/70R16	SL	704 /mi	34 lbs	2,149 lbs	44 psi	-	-	-	13.5	118 mph	6.5-8.0 in	-	10 in	10 in
		437 /km			303 kPa				11 mm					
245/70R17	SL	680 /mi	34 lbs	2,337 lbs	44 psi	-	-	-	13.5	118 mph	6.5-8.0 in	-	10 in	10 in
		423 /km			303 kPa				11 mm					
245/75R16	SL	684 /mi	33 lbs	2,403 lbs	44 psi	-	-	-	14	118 mph	6.5-8.0 in	-	10 in	10 in
		425 /km			303 kPa				11 mm					
255/65R17	SL	687 /mi	36 lbs	2,337 lbs	44 psi	-	-	-	13	118 mph	7.0-9.0 in	-	10 in	10 in
		427 /km			303 kPa				10 mm					
255/70R16	SL	690 /mi	37 lbs	2,403 lbs	44 psi	-	-	-	14	118 mph	6.5-8.5 in	-	10 in	10 in
		429 /km			303 kPa				11 mm					
255/70R17	SL	665 /mi	38 lbs	2,469 lbs	44 psi	-	-	-	14	118 mph	6.5-8.5 in	-	10 in	10 in
		413 /km			303 kPa				11 mm					

255/70R18	SL	645 /mi 401 /km	39 lbs	2,535 lbs	44 psi 303 kPa	-	-	-	14 11 mm	118 mph	6.5-8.5 in	-	10 in	10 in 259 mm
255/75R17	SL	649 /mi 403 /km	38 lbs	2,679 lbs	44 psi 303 kPa	-	-	-	14 11 mm	118 mph	6.5-8.5 in	-	10 in	10 in 254 mm
265/50R20	XL	680 /mi 423 /km	38 lbs	2,403 lbs	50 psi 344 kPa	-	-	-	12.5 10 mm	118 mph	7.5-9.5 in	-	11 in	11 in 269 mm
265/60R18	SL	679 /mi 422 /km	38 lbs	2,337 lbs	44 psi 303 kPa	-	-	-	12.5 10 mm	118 mph	7.5-9.5 in	-	11 in	11 in 272 mm
265/65R17	SL	678 /mi 421 /km	38 lbs	2,469 lbs	44 psi 303 kPa	-	-	-	13 10 mm	118 mph	7.5-9.5 in	-	11 in	11 in 269 mm
265/65R18	SL	657 /mi 408 /km	38 lbs	2,601 lbs	44 psi 303 kPa	-	-	-	13 10 mm	118 mph	7.5-9.5 in	-	11 in	11 in 272 mm
265/70R16	SL	682 /mi 424 /km	38 lbs	2,469 lbs	44 psi 303 kPa	-	-	-	14 11 mm	118 mph	7.0-9.0 in	-	11 in	11 in 274 mm
265/70R17	SL	660 /mi 410 /km	40 lbs	2,679 lbs	44 psi 303 kPa	-	-	-	14 11 mm	118 mph	7.0-9.0 in	-	11 in	11 in 272 mm
265/70R18	SL	635 /mi 395 /km	40 lbs	2,756 lbs	44 psi 303 kPa	-	-	-	14 11 mm	118 mph	7.0-9.0 in	-	11 in	11 in 272 mm
265/75R16	SL	657 /mi 408 /km	39 lbs	2,756 lbs	44 psi 303 kPa	-	-	-	14 11 mm	118 mph	7.0-9.0 in	-	11 in	11 in 267 mm
275/55R20	XL	649 /mi 403 /km	42 lbs	2,833 lbs	50 psi 344 kPa	-	-	-	12.5 10 mm	118 mph	7.5-9.5 in	-	11 in	11 in 277 mm
275/60R20	SL	628 /mi 390 /km	42 lbs	2,679 lbs	44 psi 303 kPa	-	-	-	12.5 10 mm	118 mph	7.5-9.5 in	-	11 in	11 in 277 mm
275/65R18	SL	645 /mi 401 /km	41 lbs	2,756 lbs	44 psi 303 kPa	-	-	-	13 10 mm	118 mph	7.5-9.5 in	-	11 in	11 in 279 mm
285/70R17	SL	633 /mi 393 /km	43 lbs	2,833 lbs	44 psi 303 kPa	-	-	-	14 11 mm	118 mph	7.5-9.5 in	-	12 in	12 in 292 mm