



Avenger® G/T™ Tire Specifications Table

Tire Size	Load Range	Revs	Tire Weight	Single Max Load	Single Inflation Pressure	Dual Max Load	Dual Inflation Pressure	Static Loaded Radius	Tread Depth	Max Speed	Approved Rim Width	Overall Diameter	Overall Width	Overall Width Loaded
215/65R15	SL	798 /mi	22 lbs	1,510 lbs	44 psi	-	-	-	10.5	118 mph	6.0-7.5 in	-	8 in	213 mm
		496 /km			303 kPa	-	-	8 mm	-					
215/70R14	SL	805 /mi	22 lbs	1,554 lbs	44 psi	-	-	-	10.5	118 mph	5.5-7.0 in	-	9 in	221 mm
		500 /km			303 kPa	-	-	8 mm	-					
215/70R15	SL	777 /mi	23 lbs	1,620 lbs	44 psi	-	-	-	10.5	118 mph	5.5-7.0 in	-	9 in	221 mm
		483 /km			303 kPa	-	-	8 mm	-					
225/70R14	SL	790 /mi	24 lbs	1,675 lbs	44 psi	-	-	-	10.5	118 mph	6.0-7.5 in	-	9 in	226 mm
		491 /km			303 kPa	-	-	8 mm	-					
225/70R15	SL	758 /mi	26 lbs	1,753 lbs	44 psi	-	-	-	10.5	118 mph	6.0-7.5 in	-	9 in	231 mm
		471 /km			303 kPa	-	-	8 mm	-					
235/60R14	SL	827 /mi	23 lbs	1,565 lbs	44 psi	-	-	-	10.5	118 mph	6.5-8.5 in	-	9 in	231 mm
		514 /km			303 kPa	-	-	8 mm	-					
235/60R15	SL	794 /mi	25 lbs	1,642 lbs	44 psi	-	-	-	10.5	118 mph	6.5-8.5 in	-	9 in	231 mm
		493 /km			303 kPa	-	-	8 mm	-					
235/70R15	SL	743 /mi	28 lbs	1,896 lbs	44 psi	-	-	-	10.5	118 mph	6.0-8.0 in	-	9 in	239 mm
		462 /km			303 kPa	-	-	8 mm	-					
245/60R15	SL	781 /mi	27 lbs	1,753 lbs	44 psi	-	-	-	10.5	118 mph	7.0-8.5 in	-	10 in	241 mm
		485 /km			303 kPa	-	-	8 mm	-					
255/60R15	SL	768 /mi	28 lbs	1,885 lbs	44 psi	-	-	-	10.5	118 mph	7.0-9.0 in	-	10 in	259 mm
		477 /km			303 kPa	-	-	8 mm	-					
255/70R15	SL	716 /mi	31 lbs	2,183 lbs	44 psi	-	-	-	10.5	118 mph	6.5-8.5 in	-	10 in	264 mm
		445 /km			303 kPa	-	-	8 mm	-					
275/60R15	SL	739 /mi	31 lbs	2,149 lbs	44 psi	-	-	-	10.5	118 mph	7.5-9.5 in	-	11 in	272 mm
		459 /km			303 kPa	-	-	8 mm	-					
295/50R15	SL	773 /mi	32 lbs	2,061 lbs	35 psi	-	-	-	10.5	112 mph	8.0-10.0 in	-	12 in	310 mm
		480 /km			241 kPa	-	-	8 mm	-					