



# Courseur Quest Plus Tire Specifications Table

Tire Size	Load Range	Revs	Tire Weight	Single Max Load	Single Inflation Pressure	Dual Max Load	Dual Inflation Pressure	Static Loaded Radius	Tread Depth	Max Speed	Approved Rim Width	Overall Diameter	Overall Width	Overall Width Loaded
205/70R16	SL	759 /mi	22 lbs	1,609 lbs	44 psi	-	-	-	10.5	130 mph	5.0-7.0 in	-	8 in	8 in
		472 /km			303 kPa				8 mm					
215/55R18	SL	760 /mi	25 lbs	1,521 lbs	44 psi	-	-	-	10.5	130 mph	6.0-7.5 in	-	9 in	9 in
		472 /km			303 kPa				8 mm					
215/60R17	SL	763 /mi	23 lbs	1,565 lbs	44 psi	-	-	-	10.5	130 mph	6.0-7.5 in	-	9 in	9 in
		474 /km			303 kPa				8 mm					
215/65R16	SL	768 /mi	22 lbs	1,653 lbs	44 psi	-	-	-	10.5	130 mph	6.0-7.5 in	-	9 in	9 in
		477 /km			303 kPa				8 mm					
215/65R17	SL	740 /mi	24 lbs	1,709 lbs	44 psi	-	-	-	10.5	118 mph	6.0-7.5 in	-	9 in	9 in
		460 /km			303 kPa				8 mm					
215/70R16	SL	748 /mi	24 lbs	1,764 lbs	44 psi	-	-	-	10.5	130 mph	5.5-7.0 in	-	9 in	9 in
		465 /km			303 kPa				8 mm					
225/55R18	SL	747 /mi	24 lbs	1,653 lbs	44 psi	-	-	-	10.5	130 mph	6.0-8.0 in	-	9 in	9 in
		464 /km			303 kPa				8 mm					
225/55R19	SL	718 /mi	27 lbs	1,709 lbs	44 psi	-	-	-	10.5	130 mph	6.0-8.0 in	-	9 in	9 in
		446 /km			303 kPa				8 mm					
225/60R17	SL	750 /mi	25 lbs	1,709 lbs	44 psi	-	-	-	10.5	130 mph	6.0-8.0 in	-	9 in	9 in
		466 /km			303 kPa				8 mm					
225/60R18	SL	724 /mi	25 lbs	1,764 lbs	44 psi	-	-	-	10.5	130 mph	6.0-8.0 in	-	9 in	9 in
		450 /km			303 kPa				8 mm					
225/65R17	SL	726 /mi	25 lbs	1,874 lbs	44 psi	-	-	-	10.5	130 mph	6.0-8.0 in	-	9 in	9 in
		451 /km			303 kPa				8 mm					
235/50R18	SL	760 /mi	26 lbs	1,609 lbs	44 psi	-	-	-	10.5	149 mph	6.5-8.5 in	-	10 in	10 in
		472 /km			303 kPa				8 mm					
235/55R17	SL	763 /mi	26 lbs	1,709 lbs	44 psi	-	-	-	10.5	130 mph	6.5-8.5 in	-	10 in	10 in
		474 /km			303 kPa				8 mm					
235/55R18	XL	732 /mi	28 lbs	1,984 lbs	50 psi	-	-	-	10.5	149 mph	6.5-8.5 in	-	10 in	10 in
		455 /km			344 kPa				8 mm					

235/55R19	XL	711 /mi 442 /km	30 lbs	2,039 lbs	50 psi 344 kPa	-	-	-	10.5 8 mm	149 mph	6.5-8.5 in	-	10 in	10 in 244 mm
235/55R20	SL	687 /mi 427 /km	30 lbs	1,874 lbs	44 psi 303 kPa	-	-	-	11.5 9 mm	130 mph	6.5-8.5 in	-	10 in	10 in 246 mm
235/60R17	SL	738 /mi 459 /km	26 lbs	1,874 lbs	44 psi 303 kPa	-	-	-	10.5 8 mm	130 mph	6.5-8.5 in	-	9 in	9 in 239 mm
235/60R18	XL	708 /mi 440 /km	31 lbs	2,149 lbs	50 psi 344 kPa	-	-	-	11 9 mm	149 mph	6.5-8.5 in	-	9 in	9 in 239 mm
235/65R16	SL	740 /mi 460 /km	26 lbs	1,929 lbs	44 psi 303 kPa	-	-	-	10.5 8 mm	118 mph	6.5-8.5 in	-	9 in	9 in 239 mm
235/65R17	SL	711 /mi 442 /km	28 lbs	1,984 lbs	44 psi 303 kPa	-	-	-	10.5 8 mm	130 mph	6.5-8.5 in	-	9 in	9 in 239 mm
235/65R18	SL	689 /mi 428 /km	31 lbs	2,094 lbs	44 psi 303 kPa	-	-	-	11.5 9 mm	130 mph	6.5-8.5 in	-	9 in	9 in 239 mm
235/70R16	SL	719 /mi 447 /km	29 lbs	2,094 lbs	44 psi 303 kPa	-	-	-	12.5 10 mm	118 mph	6.0-8.0 in	-	9 in	9 in 239 mm
245/50R20	SL	698 /mi 434 /km	28 lbs	1,874 lbs	44 psi 303 kPa	-	-	-	10.5 8 mm	149 mph	7.0-8.5 in	-	10 in	10 in 249 mm
245/55R19	XL	698 /mi 434 /km	33 lbs	2,149 lbs	50 psi 344 kPa	-	-	-	11.5 9 mm	130 mph	7.0-8.5 in	-	10 in	10 in 249 mm
245/60R18	SL	698 /mi 434 /km	30 lbs	2,039 lbs	44 psi 303 kPa	-	-	-	11.5 9 mm	130 mph	7.0-8.5 in	-	10 in	10 in 244 mm
245/65R17	SL	702 /mi 436 /km	31 lbs	2,149 lbs	44 psi 303 kPa	-	-	-	11.5 9 mm	118 mph	7.0-8.5 in	-	10 in	10 in 241 mm
245/70R16	SL	706 /mi 439 /km	32 lbs	2,149 lbs	44 psi 303 kPa	-	-	-	12.5 10 mm	118 mph	6.5-8.0 in	-	10 in	10 in 251 mm
245/70R17	SL	681 /mi 423 /km	34 lbs	2,337 lbs	44 psi 303 kPa	-	-	-	12.5 10 mm	118 mph	6.5-8.0 in	-	10 in	10 in 246 mm
255/50R20	XL	689 /mi 428 /km	35 lbs	2,271 lbs	50 psi 344 kPa	-	-	-	11.5 9 mm	130 mph	7.0-9.0 in	-	10 in	10 in 264 mm
255/55R18	XL	714 /mi 444 /km	34 lbs	2,271 lbs	50 psi 344 kPa	-	-	-	11 9 mm	149 mph	7.0-9.0 in	-	10 in	10 in 264 mm
255/55R20	XL	667 /mi 414 /km	37 lbs	2,337 lbs	50 psi 344 kPa	-	-	-	11.5 9 mm	130 mph	7.0-9.0 in	-	10 in	10 in 264 mm

255/60R19	SL	667 /mi 414 /km	34 lbs	2,271 lbs	44 psi 303 kPa	-	-	-	11.5 9 mm	130 mph	7.0-9.0 in	-	10 in	10 in 259 mm
255/65R17	SL	687 /mi 427 /km	31 lbs	2,337 lbs	44 psi 303 kPa	-	-	-	11.5 9 mm	118 mph	7.0-9.0 in	-	10 in	10 in 257 mm
255/65R18	SL	667 /mi 414 /km	34 lbs	2,403 lbs	44 psi 303 kPa	-	-	-	11.5 9 mm	130 mph	7.0-9.0 in	-	10 in	10 in 257 mm
255/70R16	SL	692 /mi 430 /km	34 lbs	2,403 lbs	44 psi 303 kPa	-	-	-	12.5 10 mm	118 mph	6.5-8.5 in	-	10 in	10 in 259 mm
255/70R17	SL	667 /mi 414 /km	36 lbs	2,469 lbs	44 psi 303 kPa	-	-	-	12.5 10 mm	118 mph	6.5-8.5 in	-	10 in	10 in 259 mm
265/50R20	XL	677 /mi 421 /km	36 lbs	2,403 lbs	50 psi 344 kPa	-	-	-	11.5 9 mm	118 mph	7.5-9.5 in	-	11 in	11 in 272 mm
265/60R18	SL	679 /mi 422 /km	35 lbs	2,337 lbs	44 psi 303 kPa	-	-	-	11.5 9 mm	118 mph	7.5-9.5 in	-	11 in	11 in 267 mm
265/65R17	SL	678 /mi 421 /km	32 lbs	2,469 lbs	44 psi 303 kPa	-	-	-	11.5 9 mm	118 mph	7.5-9.5 in	-	11 in	11 in 269 mm
265/65R18	SL	658 /mi 409 /km	36 lbs	2,601 lbs	44 psi 303 kPa	-	-	-	11.5 9 mm	118 mph	7.5-9.5 in	-	11 in	11 in 272 mm
265/70R16	SL	683 /mi 424 /km	36 lbs	2,469 lbs	44 psi 303 kPa	-	-	-	12.5 10 mm	118 mph	7.0-9.0 in	-	11 in	11 in 274 mm
265/70R17	SL	661 /mi 411 /km	35 lbs	2,679 lbs	44 psi 303 kPa	-	-	-	12.5 10 mm	118 mph	7.0-9.0 in	-	11 in	11 in 272 mm
275/55R20	XL	649 /mi 403 /km	41 lbs	2,833 lbs	50 psi 344 kPa	-	-	-	11.5 9 mm	130 mph	7.5-9.5 in	-	11 in	11 in 277 mm
275/60R20	SL	628 /mi 390 /km	40 lbs	2,679 lbs	44 psi 303 kPa	-	-	-	11.5 9 mm	130 mph	7.5-9.5 in	-	11 in	11 in 277 mm
275/65R18	SL	645 /mi 401 /km	37 lbs	2,756 lbs	44 psi 303 kPa	-	-	-	11.5 9 mm	118 mph	7.5-9.5 in	-	11 in	11 in 279 mm
285/45R22	XL	645 /mi 401 /km	42 lbs	2,601 lbs	50 psi 344 kPa	-	-	-	11.5 9 mm	130 mph	9.0-10.5 in	-	11 in	11 in 284 mm