



Avenger® M8™ Tire Specifications Table

Tire Size	Load Range	Revs	Tire Weight	Single Max Load	Single Inflation Pressure	Dual Max Load	Dual Inflation Pressure	Static Loaded Radius	Tread Depth	Max Speed	Approved Rim Width	Overall Diameter	Overall Width	Overall Width Loaded
205/55R16	XL	833 /mi 518 /km	23 lbs	1,477 lbs	50 psi 344 kPa	-	-	-	10.5 8 mm	168 mph	5.5-7.5 in	-	8 in	8 in 213 mm
215/45R17	XL	841 /mi 523 /km	24 lbs	1,356 lbs	50 psi 344 kPa	-	-	-	10.5 8 mm	168 mph	7.0-8.0 in	-	8 in	8 in 213 mm
215/50R17	XL	813 /mi 505 /km	25 lbs	1,521 lbs	50 psi 344 kPa	-	-	-	10.5 8 mm	168 mph	6.0-7.5 in	-	9 in	9 in 226 mm
215/60R16	SL	793 /mi 493 /km	25 lbs	1,521 lbs	44 psi 303 kPa	-	-	-	10.5 8 mm	149 mph	6.0-7.5 in	-	9 in	9 in 221 mm
225/40R18	XL	827 /mi 514 /km	25 lbs	1,389 lbs	50 psi 344 kPa	-	-	-	10.5 8 mm	168 mph	7.5-9.0 in	-	9 in	9 in 231 mm
225/45R17	XL	831 /mi 516 /km	25 lbs	1,477 lbs	50 psi 344 kPa	-	-	-	10.5 8 mm	168 mph	7.0-8.5 in	-	9 in	9 in 226 mm
225/45R18	XL	799 /mi 496 /km	27 lbs	1,521 lbs	50 psi 344 kPa	-	-	-	10.5 8 mm	168 mph	7.0-8.5 in	-	9 in	9 in 226 mm
225/50R17	SL	800 /mi 497 /km	27 lbs	1,477 lbs	51 psi 351 kPa	-	-	-	10.5 8 mm	168 mph	6.0-8.0 in	-	9 in	9 in 234 mm
225/55R17	SL	740 /mi 460 /km	28 lbs	1,609 lbs	51 psi 351 kPa	-	-	-	10.5 8 mm	168 mph	6.0-8.0 in	-	10 in	10 in 264 mm
235/45R17	SL	818 /mi 508 /km	26 lbs	1,477 lbs	51 psi 351 kPa	-	-	-	10.5 8 mm	168 mph	7.5-9.0 in	-	9 in	9 in 236 mm
235/45R18	XL	787 /mi 489 /km	28 lbs	1,653 lbs	50 psi 344 kPa	-	-	-	10.5 8 mm	168 mph	7.5-9.0 in	-	9 in	9 in 236 mm
235/50R17	SL	788 /mi 490 /km	28 lbs	1,565 lbs	51 psi 351 kPa	-	-	-	10.5 8 mm	168 mph	6.5-8.5 in	-	10 in	10 in 244 mm
235/55R17	SL	763 /mi 474 /km	29 lbs	1,709 lbs	51 psi 351 kPa	-	-	-	10.5 8 mm	168 mph	6.5-8.5 in	-	10 in	10 in 244 mm

245/40R18	XL	806 /mi 501 /km	29 lbs	1,609 lbs	50 psi 344 kPa	-	-	-	10.5 8 mm	168 mph	8.0-9.5 in	-	10 in	10 in 259 mm
245/45R17	SL	808 /mi 502 /km	28 lbs	1,521 lbs	51 psi 351 kPa	-	-	-	10.5 8 mm	168 mph	7.5-9.0 in	-	10 in	10 in 244 mm
245/45R18	SL	778 /mi 483 /km	28 lbs	1,565 lbs	51 psi 351 kPa	-	-	-	10.5 8 mm	168 mph	7.5-9.0 in	-	10 in	10 in 244 mm
245/45R19	SL	749 /mi 465 /km	30 lbs	1,653 lbs	51 psi 351 kPa	-	-	-	10.5 8 mm	168 mph	7.5-9.0 in	-	10 in	10 in 244 mm
245/50R18	SL	749 /mi 465 /km	31 lbs	1,764 lbs	51 psi 351 kPa	-	-	-	10.5 8 mm	168 mph	7.0-8.5 in	-	10 in	10 in 254 mm