



STRATUS HT

Tire Specifications Table

Tire Size	Load Range	Revs	Tire Weight	Single Max Load	Single Inflation Pressure	Dual Max Load	Dual Inflation Pressure	Static Loaded Radius	Tread Depth	Max Speed	Approved Rim Width	Overall Diameter	Overall Width	Overall Width Loaded
215/85R16	E	687 /mi	35 lbs	2,680 lbs	80 psi	2,470 lbs	80 psi	-	13.5	106 mph	5.5-7.0 in	-	8 in	8 in
		427 /km			551 kPa		551 kPa		-					
225/75R16	SL	716 /mi	27 lbs	1,984 lbs	44 psi	-	-	-	10.5	118 mph	6.0-7.5 in	-	9 in	9 in
		445 /km			303 kPa		-		-					
225/75R16	E	709 /mi	35 lbs	2,680 lbs	80 psi	2,470 lbs	80 psi	-	13.5	106 mph	6.0-7.0 in	-	9 in	9 in
		441 /km			551 kPa		551 kPa		-					
235/65R18	SL	689 /mi	32 lbs	2,094 lbs	44 psi	-	-	-	10.5	118 mph	6.5-8.5 in	-	9 in	9 in
		428 /km			303 kPa		-		-					
235/70R16	SL	721 /mi	27 lbs	2,094 lbs	44 psi	-	-	-	10.5	118 mph	6.0-8.0 in	-	9 in	9 in
		448 /km			303 kPa		-		-					
235/75R15	XL	724 /mi	29 lbs	2,271 lbs	50 psi	-	-	-	10.5	118 mph	6.0-8.0 in	-	9 in	9 in
		450 /km			344 kPa		-		-					
235/80R17	E	655 /mi	39 lbs	3,085 lbs	80 psi	2,835 lbs	80 psi	-	13.5	106 mph	6.0-7.5 in	-	9 in	9 in
		407 /km			551 kPa		551 kPa		-					
235/85R16	E	658 /mi	39 lbs	3,042 lbs	80 psi	2,778 lbs	80 psi	-	13.5	106 mph	6.0-7.5 in	-	9 in	9 in
		409 /km			551 kPa		551 kPa		-					
245/50R20	SL	698 /mi	29 lbs	1,874 lbs	44 psi	-	-	-	10.5	130 mph	7.0-8.5 in	-	10 in	10 in
		434 /km			303 kPa		-		-					
245/55R19	SL	698 /mi	30 lbs	1,929 lbs	44 psi	-	-	-	10.5	118 mph	7.0-8.5 in	-	10 in	10 in
		434 /km			303 kPa		-		-					
245/60R18	SL	698 /mi	30 lbs	2,039 lbs	44 psi	-	-	-	10.5	130 mph	7.0-8.5 in	-	10 in	10 in
		434 /km			303 kPa		-		-					
245/65R17	SL	703 /mi	30 lbs	2,149 lbs	44 psi	-	-	-	10.5	118 mph	7.0-8.5 in	-	10 in	10 in
		437 /km			303 kPa		-		-					
245/70R16	SL	707 /mi	30 lbs	2,149 lbs	44 psi	-	-	-	10.5	118 mph	6.5-8.0 in	-	10 in	10 in
		439 /km			303 kPa		-		-					
245/70R17	SL	686 /mi	31 lbs	2,337 lbs	44 psi	-	-	-	10.5	118 mph	6.5-8.0 in	-	10 in	10 in
		426 /km			303 kPa		-		-					

245/75R16	E	684 /mi 425 /km	38 lbs	3,042 lbs	80 psi 551 kPa	2,778 lbs	80 psi 551 kPa	-	13.5 11 mm	112 mph	6.5-8.0 in	-	10 in	10 in 244 mm
245/75R16	SL	687 /mi 427 /km	31 lbs	2,403 lbs	44 psi 303 kPa	-	-	-	10.5 8 mm	118 mph	6.5-8.0 in	-	10 in	10 in 249 mm
245/75R17	E	657 /mi 408 /km	43 lbs	3,195 lbs	80 psi 551 kPa	2,910 lbs	80 psi 551 kPa	-	13.5 11 mm	112 mph	6.5-7.5 in	-	10 in	10 in 254 mm
255/50R20	XL	689 /mi 428 /km	34 lbs	2,271 lbs	50 psi 344 kPa	-	-	-	10.5 8 mm	130 mph	7.0-9.0 in	-	10 in	10 in 264 mm
255/65R18	SL	667 /mi 414 /km	34 lbs	2,403 lbs	44 psi 303 kPa	-	-	-	10.5 8 mm	118 mph	7.0-9.0 in	-	10 in	10 in 257 mm
255/70R16	SL	696 /mi 432 /km	32 lbs	2,403 lbs	44 psi 303 kPa	-	-	-	10.5 8 mm	118 mph	6.5-8.5 in	-	10 in	10 in 262 mm
255/70R18	SL	646 /mi 401 /km	34 lbs	2,535 lbs	44 psi 303 kPa	-	-	-	10.5 8 mm	118 mph	6.5-8.5 in	-	10 in	10 in 259 mm
265/60R18	SL	679 /mi 422 /km	31 lbs	2,337 lbs	44 psi 303 kPa	-	-	-	10.5 8 mm	118 mph	7.5-9.5 in	-	11 in	11 in 267 mm
265/65R17	SL	682 /mi 424 /km	35 lbs	2,469 lbs	44 psi 303 kPa	-	-	-	10.5 8 mm	118 mph	7.5-9.5 in	-	11 in	11 in 269 mm
265/65R18	SL	658 /mi 409 /km	36 lbs	2,601 lbs	44 psi 303 kPa	-	-	-	10.5 8 mm	118 mph	7.5-9.5 in	-	11 in	11 in 272 mm
265/70R16	SL	686 /mi 426 /km	33 lbs	2,469 lbs	44 psi 303 kPa	-	-	-	10.5 8 mm	118 mph	7.0-9.0 in	-	11 in	11 in 274 mm
265/70R17	SL	662 /mi 411 /km	33 lbs	2,679 lbs	44 psi 303 kPa	-	-	-	10.5 8 mm	118 mph	7.0-9.0 in	-	11 in	11 in 269 mm
265/70R17	E	658 /mi 409 /km	45 lbs	3,195 lbs	80 psi 551 kPa	2,910 lbs	80 psi 551 kPa	-	13.5 11 mm	106 mph	7.0-8.5 in	-	11 in	11 in 277 mm
265/70R18	SL	637 /mi 396 /km	35 lbs	2,756 lbs	44 psi 303 kPa	-	-	-	10.5 8 mm	118 mph	7.0-9.0 in	-	11 in	11 in 272 mm
265/75R16	E	658 /mi 409 /km	42 lbs	3,415 lbs	80 psi 551 kPa	3,085 lbs	80 psi 551 kPa	-	13.5 11 mm	112 mph	7.0-8.0 in	-	11 in	11 in 269 mm
265/75R16	SL	662 /mi 411 /km	31 lbs	2,756 lbs	44 psi 303 kPa	-	-	-	10.5 8 mm	118 mph	7.0-9.0 in	-	11 in	11 in 269 mm
275/55R20	XL	653 /mi 406 /km	40 lbs	2,833 lbs	50 psi 344 kPa	-	-	-	10.5 8 mm	130 mph	7.5-9.5 in	-	11 in	11 in 277 mm
275/60R20	SL	631 /mi 392 /km	38 lbs	2,679 lbs	44 psi 303 kPa	-	-	-	10.5 8 mm	118 mph	7.5-9.5 in	-	11 in	11 in 277 mm

		651 /mi	35 lbs	2,756 lbs	44 psi	-	-	-	10.5	118 mph	7.5-9.5 in	-	11 in	11 in
275/65R18	SL	405 /km			303 kPa		-	-	8 mm			-		279 mm
