



# SRT Touring™

## Tire Specifications Table

Tire Size	Load Range	Revs	Tire Weight	Single Max Load	Single Inflation Pressure	Dual Max Load	Dual Inflation Pressure	Static Loaded Radius	Tread Depth	Max Speed	Approved Rim Width in	Overall Diameter	Overall Width	Overall Width Loaded
185/65R15	SL	848 /mi	17 lbs	1,235 lbs	44 psi	-	-	-	9.5	130 mph	5.0-6.5 in	-	7 in	7 in
		527 /km			303 kPa		-	-	8 mm					188 mm
195/60R15	SL	856 /mi	18 lbs	1,235 lbs	44 psi	-	-	-	9.5	130 mph	5.5-7.0 in	-	8 in	8 in
		532 /km			303 kPa		-	-	8 mm					201 mm
195/65R15	SL	829 /mi	19 lbs	1,356 lbs	44 psi	-	-	-	9.5	130 mph	5.5-7.0 in	-	8 in	8 in
		515 /km			303 kPa		-	-	8 mm					201 mm
205/55R16	SL	833 /mi	19 lbs	1,356 lbs	44 psi	-	-	-	9.5	130 mph	5.5-7.5 in	-	8 in	8 in
		518 /km			303 kPa		-	-	8 mm					211 mm
205/60R16	SL	808 /mi	20 lbs	1,389 lbs	44 psi	-	-	-	9.5	130 mph	5.5-7.5 in	-	8 in	8 in
		502 /km			303 kPa		-	-	8 mm					208 mm
205/65R15	SL	814 /mi	19 lbs	1,477 lbs	44 psi	-	-	-	9.5	130 mph	5.5-7.5 in	-	8 in	8 in
		506 /km			303 kPa		-	-	8 mm					208 mm
205/65R16	SL	784 /mi	20 lbs	1,521 lbs	44 psi	-	-	-	9.5	130 mph	5.5-7.5 in	-	8 in	8 in
		487 /km			303 kPa		-	-	8 mm					208 mm
215/55R16	XL	825 /mi	21 lbs	1,609 lbs	50 psi	-	-	-	9.5	130 mph	6.0-7.5 in	-	9 in	9 in
		513 /km			344 kPa		-	-	8 mm					226 mm
215/55R17	SL	788 /mi	21 lbs	1,477 lbs	44 psi	-	-	-	9.5	149 mph	6.0-7.5 in	-	9 in	9 in
		490 /km			303 kPa		-	-	8 mm					226 mm
215/60R16	SL	794 /mi	21 lbs	1,521 lbs	44 psi	-	-	-	9.5	149 mph	6.0-7.5 in	-	9 in	9 in
		493 /km			303 kPa		-	-	8 mm					224 mm
215/60R17	SL	768 /mi	22 lbs	1,565 lbs	44 psi	-	-	-	9.5	118 mph	6.0-7.5 in	-	9 in	9 in
		477 /km			303 kPa		-	-	8 mm					216 mm
215/65R16	SL	771 /mi	21 lbs	1,653 lbs	44 psi	-	-	-	9.5	118 mph	6.0-7.5 in	-	9 in	9 in
		479 /km			303 kPa		-	-	8 mm					221 mm
215/70R15	SL	771 /mi	20 lbs	1,653 lbs	44 psi	-	-	-	9.5	118 mph	5.5-7.0 in	-	9 in	9 in
		479 /km			303 kPa		-	-	8 mm					218 mm
225/50R17	SL	800 /mi	21 lbs	1,477 lbs	44 psi	-	-	-	9.5	149 mph	6.0-8.0 in	-	9 in	9 in
		497 /km			303 kPa		-	-	8 mm					231 mm

225/60R16	SL	779 /mi 484 /km	22 lbs	1,653 lbs	44 psi 303 kPa	-	-	-	9.5 8 mm	130 mph	6.0-8.0 in	-	9 in	9 in 224 mm
225/60R17	SL	753 /mi 468 /km	23 lbs	1,709 lbs	44 psi 303 kPa	-	-	-	9.5 8 mm	118 mph	6.0-8.0 in	-	9 in	9 in 229 mm
225/60R18	SL	724 /mi 450 /km	25 lbs	1,764 lbs	44 psi 303 kPa	-	-	-	9.5 8 mm	130 mph	6.0-8.0 in	-	9 in	9 in 229 mm
225/65R16	SL	754 /mi 469 /km	23 lbs	1,764 lbs	44 psi 303 kPa	-	-	-	9.5 8 mm	118 mph	6.0-8.0 in	-	9 in	9 in 226 mm
225/65R17	SL	727 /mi 452 /km	24 lbs	1,874 lbs	44 psi 303 kPa	-	-	-	9.5 8 mm	118 mph	6.0-8.0 in	-	9 in	9 in 229 mm
235/55R18	SL	737 /mi 458 /km	26 lbs	1,764 lbs	44 psi 303 kPa	-	-	-	9.5 8 mm	149 mph	6.5-8.5 in	-	10 in	10 in 244 mm
235/65R16	SL	740 /mi 460 /km	24 lbs	1,929 lbs	44 psi 303 kPa	-	-	-	9.5 8 mm	118 mph	6.5-8.5 in	-	10 in	10 in 244 mm
235/65R17	SL	717 /mi 446 /km	26 lbs	1,984 lbs	44 psi 303 kPa	-	-	-	9.5 8 mm	118 mph	6.5-8.5 in	-	9 in	9 in 239 mm