



Courser® MXT™

Tire Specifications Table

Tire Size	Load Range	Revs	Tire Weight	Single Max Load	Single Inflation Pressure	Dual Max Load	Dual Inflation Pressure	Static Loaded Radius	Tread Depth	Max Speed	Approved Rim Width	Overall Diameter	Overall Width	Overall Width Loaded
12.5/75R17	D	565 /mi	72 lbs	3,525 lbs	50 psi	-	-	-	21	94 mph	8.5-11.0 in	37 in	13 in	13 in
		351 /km			344 kPa				17 mm			940 mm		
12.5/75R20	E	564 /mi	72 lbs	3,750 lbs	65 psi	-	-	-	21	94 mph	8.5-11.0 in	37 in	13 in	13 in
		350 /km			448 kPa				17 mm			940 mm		
13.5/75R20	E	563 /mi	63 lbs	3,860 lbs	65 psi	-	-	-	21	99 mph	8.5-11.0 in	37 in	14 in	14 in
		350 /km			448 kPa				17 mm			940 mm		
235/85R16	E	653 /mi	44 lbs	3,042 lbs	80 psi	2,778 lbs	80 psi	-	18	99 mph	6.0-7.5 in	-	10 in	10 in
		406 /km			551 kPa				14 mm			-		
245/75R16	E	678 /mi	44 lbs	3,042 lbs	80 psi	2,778 lbs	80 psi	-	18	99 mph	6.5-8.0 in	-	9 in	9 in
		421 /km			551 kPa				14 mm			-		
245/75R17	E	654 /mi	46 lbs	3,195 lbs	80 psi	2,910 lbs	80 psi	-	18.5	99 mph	6.5-8.0 in	-	10 in	10 in
		406 /km			551 kPa				15 mm			-		
265/70R17	E	653 /mi	49 lbs	3,195 lbs	80 psi	2,910 lbs	80 psi	-	18.5	99 mph	7.0-8.5 in	-	11 in	11 in
		406 /km			551 kPa				15 mm			-		
265/75R16	E	653 /mi	48 lbs	3,415 lbs	80 psi	3,085 lbs	80 psi	-	18.5	99 mph	7.0-8.0 in	-	10 in	10 in
		406 /km			551 kPa				15 mm			-		
275/65R18	E	644 /mi	52 lbs	3,415 lbs	80 psi	3,085 lbs	80 psi	-	19	99 mph	7.5-9.0 in	-	11 in	11 in
		400 /km			551 kPa				15 mm			-		
275/65R20	E	604 /mi	59 lbs	3,750 lbs	80 psi	3,415 lbs	80 psi	-	18.5	99 mph	7.5-9.5 in	-	11 in	11 in
		375 /km			551 kPa				15 mm			-		
275/70R18	E	622 /mi	55 lbs	3,640 lbs	80 psi	3,305 lbs	80 psi	-	19	99 mph	7.0-8.5 in	-	11 in	11 in
		386 /km			551 kPa				15 mm			-		
285/65R18	E	631 /mi	55 lbs	3,640 lbs	80 psi	3,305 lbs	80 psi	-	18.5	99 mph	8.0-10.0 in	-	12 in	12 in
		392 /km			551 kPa				15 mm			-		
285/70R17	E	630 /mi	54 lbs	3,195 lbs	80 psi	2,910 lbs	80 psi	-	18.5	99 mph	7.5-9.0 in	-	12 in	12 in
		391 /km			551 kPa				15 mm			-		
285/75R16	E	631 /mi	55 lbs	3,750 lbs	80 psi	3,415 lbs	80 psi	-	18.5	99 mph	7.5-9.0 in	-	11 in	11 in
		392 /km			551 kPa				15 mm			-		

295/55R20	E	628 /mi 390 /km	55 lbs	3,415 lbs	80 psi 551 kPa	3,085 lbs	80 psi 551 kPa	- -	19.5 15 mm	94 mph	8.0-10.0 in	- -	12 in	12 in 310 mm
295/70R17	E	620 /mi 385 /km	59 lbs	3,195 lbs	80 psi 551 kPa	2,910 lbs	80 psi 551 kPa	- -	19.5 15 mm	99 mph	7.5-10.0 in	- -	12 in	12 in 300 mm
295/70R18	E	605 /mi 376 /km	62 lbs	4,080 lbs	80 psi 551 kPa	3,750 lbs	80 psi 551 kPa	- -	19.5 15 mm	99 mph	7.5-10.0 in	- -	12 in	12 in 305 mm
305/55R20	E	622 /mi 386 /km	60 lbs	3,195 lbs	65 psi 448 kPa	2,910 lbs	65 psi 448 kPa	- -	19.5 15 mm	99 mph	8.5-11.0 in	- -	13 in	13 in 318 mm
305/70R16	E	629 /mi 391 /km	58 lbs	3,525 lbs	65 psi 448 kPa	3,195 lbs	65 psi 448 kPa	- -	19 15 mm	99 mph	8.0-9.5 in	- -	12 in	12 in 305 mm
305/70R18	E	593 /mi 368 /km	65 lbs	3,750 lbs	65 psi 448 kPa	3,415 lbs	65 psi 448 kPa	- -	19.5 15 mm	99 mph	8.5-10.0 in	- -	13 in	13 in 318 mm
31/10.5R15	C	677 /mi 421 /km	44 lbs	2,270 lbs	50 psi 344 kPa	-	-	- -	19 15 mm	99 mph	7.0-9.0 in	31 in 787 mm	11 in	11 in 277 mm
315/70R17	D	601 /mi 373 /km	64 lbs	3,195 lbs	50 psi 344 kPa	2,910 lbs	50 psi 344 kPa	- -	19.5 15 mm	99 mph	8.0-11.0 in	- -	13 in	13 in 325 mm
315/75R16	E	598 /mi 372 /km	63 lbs	3,860 lbs	65 psi 448 kPa	3,525 lbs	65 psi 448 kPa	- -	19.5 15 mm	99 mph	8.0-11.0 in	- -	12 in	12 in 302 mm
32/11.5R15	C	656 /mi 408 /km	50 lbs	2,535 lbs	50 psi 344 kPa	-	-	- -	19 15 mm	99 mph	8.0-10.0 in	32 in 813 mm	11 in	11 in 290 mm
33/12.5R15	C	631 /mi 392 /km	55 lbs	2,205 lbs	35 psi 241 kPa	-	-	- -	20 16 mm	99 mph	8.5-11.0 in	33 in 838 mm	12 in	12 in 307 mm
35/12.5R15	C	597 /mi 371 /km	64 lbs	2,535 lbs	35 psi 241 kPa	-	-	- -	20 16 mm	99 mph	8.5-11.0 in	35 in 889 mm	12 in	12 in 310 mm
35/12.5R17	E	596 /mi 370 /km	67 lbs	3,195 lbs	65 psi 448 kPa	-	-	- -	20 16 mm	99 mph	8.5-11.0 in	35 in 889 mm	13 in	13 in 323 mm
35/12.5R20	E	598 /mi 372 /km	64 lbs	3,195 lbs	65 psi 448 kPa	-	-	- -	20 16 mm	99 mph	8.5-11.0 in	35 in 889 mm	13 in	13 in 318 mm